

# MxP<sup>®</sup> Quant 500 XL kit requirements

This document specifies additional lab equipment and chemicals that are required but <u>not</u> included with the kit. Before starting with the kit, ensure that all required items are available.

## LC-MS system

Agilent	SCIEX	Waters		
Mass spectrometer				
<b>6495C</b> Triple Quadrupole LC/MS System	7500, 6500+, 5500+ or 5500 series (QTRAP or Triple Quad) with TurboV™ ion source or Optiflow Pro (high flow)	<b>Xevo TQ Absolute</b> or <b>TQ-XS</b> with ESI source		
LC and autosampler				
<ul> <li>Agilent 1290 Infinity I/II UHPLC system with column oven. NanoLC and microLC are not supported!</li> <li>800 bar injection valve (Agilent part no. 5067- 6698) replaces standard 1300 bar valve</li> <li>1290 Infinity II inline filters, 0.3 µm (2 pcs., before and after injection valve, Agilent part no. 5067-6189)</li> <li>96-well plate autosampler with temperature control (10 °C)</li> <li>Injection volume range: 2 - 20 µL</li> </ul>	<ul> <li>Standard flow HPLC or UHPLC system with column oven. NanoLC and microLC are not supported!</li> <li>96-well plate autosampler with temperature control (10 °C)</li> <li>Injection volume range: 5 - 20 µL</li> <li>Special sample rack for deep-well plates required for the following autosamplers:</li> <li>Shimadzu: part no. 228-37546-92 (Deep-well MTP Rack, DWP-96)</li> <li>UltiMate 3000: Thermo part no. 6820.4083 (30 - 36 mm height)</li> </ul>	<ul> <li>Waters ACQUITY UPLC® system with sample manager, solvent manager, and column oven:</li> <li>Classic (loop-based)</li> <li>I-Class (FTN)</li> <li>H-Class (FTN)</li> <li>Injection volume range: 2 - 20 µL</li> <li>FTN samplers require extension loop of 50 µL or needle size of 30 µL!</li> </ul>		
Tubing				

- Recommended between injector and column system: steel capillary

 Recommended between column system and mass spectrometer: red PEEK Tubing 1/16" OD x 0.005" ID



# LC-MS instrument status

#### Condition

- Serviced, calibrated and tuned instruments according to manufacturer's recommendations on a regular basis
- LC-MS system must be free of ion-pair reagent

# Analytical column

#### HPLC and UHPLC

Analytical column hiter 21117.1 (UHPLC), 21117.2 (HPLC) (HPLC/UHPLC column + pre-column mixer + connector, factory assembled)

## Laboratory equipment

Laboratory equipment (may also be available from your local kit distributor)				
	Nitrogen evaporator for 96-well plates	Pressure manifold for 96-well plates		
Nitrogen evaporator* or pressure manifold* - Requires nitrogen supply - Must be in a fume hood - No heater required	<ul> <li>Examples:</li> <li>Porvair blowdown evaporator MiniVap®</li> <li>Techne (FSC496D)</li> <li>Sample concentrator from BenchTop Lab Systems (96 samples, BT1604)</li> <li>VLM evaporators</li> <li>Organomation MICROVAP microplate evaporator</li> <li>Biotage TurboVap® 96</li> </ul>	<ul> <li>Examples:</li> <li>Porvair UltraPPM LITE</li> <li>Waters positive pressure-96 processor (186006961)</li> <li>Biotage® PRESSURE+ 96 manifold (PPM-96)</li> <li>CEREX® system 96 processor (288-0001)</li> <li>Agilent positive pressure manifold 96 processor (PPM-96)</li> <li>TECAN Resolvex® M10 96</li> </ul>		
Centrifuge	Must be able to centrifuge 96-well plates of 5 cm height at 500 x g	Not required when a pressure manifold is used.		
Shaker	Any model with adjustable speed (450 – 1200 rpm) including a tray for plates and vials. Recommended: Eppendorf MixMate® or ThermoMixer®			
Pipettes	<ul> <li>Repeater, e.g. Eppendorf Multipette<sup>®</sup> E3 (with 2.5 and 10 mL tips) or similar electronic model</li> <li>Single channel: volume range 10 μL – 1000 μL</li> <li>8-Channel: 10 μL – 150 μL</li> </ul>			
Vortexer	Any model			
Balance	Accuracy < 1 mg			
Solvent bottles	50 – 1000 mL			

\* See document "Technical guide-Nitrogen evaporators and pressure manifolds" for details.



## Solvents and chemicals

Solvents and chemicals	Purity	
Ethanol, methanol, water, acetonitrile, isopropanol	LC-MS grade (ethanol: HPLC grade sufficient)	
Formic acid	LC-MS grade (e.g. Honeywell Fluka <sup>™</sup> 56302-50ML) Fresh! New bottle or opened within past 6 months	
Phenyl isothiocyanate (PITC)	99%, for protein sequencing (e.g. Sigma-Aldrich 317861) Fresh! New bottle or opened within past 6 months	
Pyridine	Purity >99% (recommended Acros Organics 131780500, 50mL) Fresh! New bottle or opened within past 6 months	
Ammonium acetate	LC-MS grade	
Phosphate buffered saline (PBS)	p.a. grade (e.g. Sigma-Aldrich P4417)	

### Software

Agilent	SCIEX	Waters		
MS software				
MassHunter version 10.1 or 12	Analyst® version 1.7 or later SCIEX OS version 3 or later	MassLynx® version 4.1 or later		
biocrates WebIDQ workflow manager				

Please get one of the three subscription versions through our webshop or your local distributor:

- WebIDQ cloud subscription (10 GB storage space) biocrates part number 21629
- WebIDQ cloud+ subscription (50 GB storage space) biocrates part number 21926
- WebIDQ on-premises subscription biocrates part number 21636

For detailed system requirements please visit: <u>https://shop.biocrates.com/fag/What-are-the-system-requirements-for-WebIDQ</u>